

CH-SERIES Technical Specifications

Model			CH36
Climate type			T1
Indoor unit			1100
Outdoor Unit			W28
Power supply		Ph-V-Hz	1Ph-220~240V-50Hz
Type			Cooling-Heating
Power Supply Mode			alternating current
Control type			Remote Controller
Cooling	Capacity	W/h	9143
	Power Input	W	3027
	Rated Current	A	9.93
	EER	W/W	3.02
Heating	Capacity	W/h	9600
	Power Input	W	2857
	Rated Current	A	9.54
	COP	W/W	3.36
Compressor	Model		PA270G2CS-4MU1
	Type		ROTARY
	Brand		GMCC
Indoor unit	Indoor fan motor	Model	RPG45 RPG45D
		Brand	Welling/Tongde
		Capacitor	uF 3
		Motor speed	RPM 1280
	Indoor air flow	m3/h	1200
	Noise level	dB(A)	52
	Unit dimension (W*H*D)	mm	1100x325x252
	Packing (W*H*D)	mm	1190x420x325
Outdoor unit	Outdo or fan motor	Model	YDK68-6E/Y6S696C520
		Brand	Welling/Broad-ocean
		Capacitor	uF 4
		Motor speed	Rpm 880
	Noise level	dB(A)	59
	Refrigerant type		R410A
	Unit dimension (W*H*D)	mm	860*720*320
	Packing (W*H*D)	mm	1015*775*445
Refrigerant pipe	Liquid side	mm	9.52
	Gas side	mm	15.88
	Max. refrigerant pipe length	m	15
	Max. difference in level	m	8